CLAIMS

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- 1. (Currently Amended) A crimp for an optical cable connector, comprising a hollow crimp body that is open at each end and comprises, at a first end, a first crushable crimp tube for crimping onto a connector; and at a second end a second crushable crimp tube for crimping onto a cable, the portion of the crimp between the said ends defining a body portion having a dimension greater than that of the crimp tubes and including a recess for engagement by a closure housing, where the recess has a dimension less than that of the body portion.
- 2. (Original) A crimp according to Claim 1, wherein the respective crimp tubes and the said portion therebetween are cylindrical.
- 3. (Original) A crimp according to Claim 2, wherein the diameter of the said portion between the crimp tubes is greater than that of either crimp tube.
- 4. (Previously Amended) A crimp according to Claim 1, wherein the recess is a groove formed in the periphery of the said portion.
- 5. (Currently Amended) A crimp according to Claim 4, wherein the recess extends about the whole periphery of the said body portion.
- 6. (Currently Amended) A An crimp comprising a hollow crimp body that is open at each end and comprises, at a first end, a first crushable crimp tube for crimping onto a connector; and at a second end a second crushable crimp tube for crimping onto a cable, the portion of the crimp between the said ends including a grooved recess extending transverse to a longitudinal direction of the hollow crimp body for engagement by a closure housing, and

further comprising an optical cable inserted therethrough, the crimp tube at the said first end of the crimp being crimped onto the spigot of a connector so as to retain thereon the reinforcing fibers of the optical cable; and the crimp tube at the said second end being crimped onto the exterior of the optical cable.

- 7. (Original) A crimp according to Claim 6 including a portion of a closure housing received in the said recess so as to prevent relative movement between the crimp and the said closure housing portion.
- 8. (Currently Amended) A crimp according to any Claim 6, wherein the recess lies offset from the longitudinal mid-point of the crimp body.
- 9. (Original) A method of securing an optical cable to a connector comprising the steps of:
- (i) inserting an optical cable through a crimp according to any preceding claim so as to protrude at either end thereof;
- (ii) removing the jacket of the optical cable to expose the core and reinforcement fibers thereof;
 - (iii) inserting the core into a connector spigot;
 - (iv) arranging the reinforcing fibers about the spigot;
 - (v) advancing the crimp so that the first crimp tube overlies the spigot and the fibers;
- (vi) crimping the first crimp tube onto the spigot so as to retain the fibers on the spigot; and, before or after step (vi),
 - (vii) crimping the second crimp tube onto the exterior of the cable.
- 10. (Currently Amended) A method according to Claim 9 including the further step of:
- (viii) inserting the crimp into an aperture of a recess formed in a closure housing so that a part of the closure housing engages the recess so as to prevent relative <u>longitudinal</u> movement between the crimp and the closure housing.